

AIR COOLER

KSWK-6001Dgl



KSWK-6001Dgl







Four refilling methods





Air supply distance



areas

Covering




Cooling humidification purification



Side refilling



Top refilling



Automatic refilling



Split-tank refilling



60L super large water tank



60L (15.9G) = 3 barrels of bottled water



User-friendly and safe design



Power-off protection upon low water



Pump protection device: lifting and overturning



Power cord bracket and remote controller storage



Easy storage: water tank inverted on the unit body



Side handle and castors



Touch control



LED display







Power-off







Turbo blower



Convenient to clean: Removable wet curtain water tank and front-mounted filter



Honeycomb cooling pad missing protection device: prevent water splashing



Ball-bearing motor: long service life and multi-protection

KSWK-6001Dgl

- 60L water tank
- Air volume: 1100m3/h
- Evaporation capacity: 3200ml/h
- Pure copper AC ball-bearing motor
- Turbo blower system & DC pump & honeycomb cooling pad
- 4 filling methods: side filling/top filling/ automatic filling/split-tank filling
- Higher loading capacity
- Low water protection

- Touch control panel
- LED display
- 4 fan speeds
- 15h timer
- With power-off memory function
- Remote control
- Removable honeycomb cooling pad & water tank & pre-filters
- Side handles and castors





Over 1100m³/h big air volume



15M Wind travel distance



160m² Area coverage



3-in-1
Cooling, humidification; centrifugal fan





60L super large water tank



60L(15.9G)=3 barrels of water







Side refilling



Top refilling



Split-tank refilling

Features

- Centrifugal blower + Ball bearing Motor(100% copper)
- 60 liter water tank
- Detachable water tank for easy cleaning & refills
- Honeycomb cooling media
- Slim body and recessed handle design
- LED display & Remote control
- Power off memory function
- Touch control panel
- 4 speeds
- 15h timer
- Oscillation function
- Portable handle & castors for easy moving
- With 120° right&left swing angle (Auto)
- With 120° up&down swing angle (Manual)
- CB Certificate

Evaporation Capacity	3200ml/h
Air Volume (high speed)	1100m²/h
Unit dimension/Weight	395*405*980mm/
Loading Capacity	375/40HQ