

Circular Duct Fan
圆形管道风机




Specification: 100mm, 125mm, 150mm, 160mm, 200mm, 250mm, 315mm
管口直径: 100mm, 125mm, 150mm, 160mm, 200mm, 250mm, 315mm.

Ambient temperature: between -10 Celsius degree (14 Fahrenheit degree)
and 60 Celsius degree (140 Fahrenheit degree).

环境温度介于 -10摄氏度(14华氏度) 至 60摄氏度(140华氏度)之间使用。

F insulation class motor
采用F绝缘等级的电机

External Dimensions 外形尺寸图



Dimension Table 尺寸表

Units 单位:mm

型号 Model No.	A	B	C	D	E
DJT10-25B	100	242	20	186	15
DJT12-35B	125	243	25	189	22
DJT15-45B	150	271	20	193	20
DJT16-45B	160	345	27	228	27
DJT20-46B	200	345	27	228	29
DJT25-66B	250	345	27	228	29
DJT31-66B	315	400	27	259	29

Circular Duct Fan
圆形管道风机

Electrical Ratings 技术参数

型号 Model No.	额定电压/ 频率/ 相数 Rated Voltage/ Frequency/ Phase	风轮直径 Impeller Diameter (mm)	功率 Power (W)	电流 Current (A)	转速 Rotating Speed (R.P.M.)	风量 Air Volume (m³/h)	静压 Static Pressure (Pa)	噪音 Noise (dB(A))	电机绝缘等级 Insulation Class	净重 Net Weight (kg)
DJT10-25B	220V~/ 50Hz/ 1Ph	190	77	0.35	2360	248	320	55	F	3.45
DJT12-35B		190	88	0.41	2380	360	340	55		3.40
DJT15-45B		190	88	0.41	2380	450	330	57		3.80
DJT16-45B		220	127	0.60	2480	580	380	59		5.30
DJT20-46B		250	178	0.84	2445	1030	530	61		5.80
DJT25-66B		250	181	0.84	2550	1180	600	63		6.05
DJT31-66B		250	163	0.75	2625	1500	500	65		6.80

Performance Curve 性能曲线图

