



Fairy R410A

Fairy R410A



white



champagne



Model			GWH09ACA-K3NNA1A	GWH12ACB-K3NNA1A	GWH18ACC-K3NNA1A	GWH24ACD-K3NNA1A	GWH28ACE-K3NNA1A
Function			Cooling & Heating	Cooling & Heating	Cooling & Heating	Cooling & Heating	Cooling & Heating
Capacity	Cooling	Btu/h	9000	12000	18000	24000	28000
	Heating	Btu/h	9500	13000	19000	25000	29000
EER/COP		W/W	3.21/3.61	3.21/3.61	3.21/3.61	3.21/3.61	2.81/3.21
Power Supply			220-240V~, 50Hz	220-240V~, 50Hz	220-240V~, 50Hz	220-240V~, 50Hz	220-240V~, 50Hz
Power Input	Cooling	W	794	1012	1495	1915	2846
	Heating	W	734	941	1468	1856	2647
Rated Current	Cooling	A	6.2	6.30	10.75	13.88	20
	Heating	A	5.2	6.0	10.96	11.82	15
Airflow Volume		m3/h	470/420/370/250	550/500/430/330	650/560/480/350	900/800/700/600	1200/1100/1000/850
Indoor Unit							
Sound Pressure Level	Indoor	dB(A)	40/38/35/26	42/39/36/33	42/38/34/31	49/45/41/37	51/48/42/39/
Outline Dimension	WxHxD	mm	744x256x185	819x256x185	849x289x210	1013x307x221	1122x329x247
Package Dimension	WxHxD	mm	793x330x260	868x330x260	940x365x284	1080x315x378	1193x410x350
Net Weight/Gross Weight	Indoor	Kg	8/9.5	8.5/10	11/13	14/17	16.5/20
Outdoor Unit							
Sound Pressure Level	Outdoor	dB(A)	49	52	56	56	59
Outline Dimension	WxHxD	mm	720x428x310	776x540x320	848x540x320	913x680x378	955x700x396
Package Dimension	WxHxD	mm	768x490x353	823x595x358	881x595x363	997x740x431	1029x750x458
Net Weight/Gross Weight	Outdoor	Kg	24.5/26.5	30/32.5	39/41.5	50/54	61/65.5
Connection Type	Liquid	Inch	1/4"	1/4"	1/4"	1/4"	1/4"
	Gaz	Inch	3/8"	1/2"	1/2"	1/2"	5/8"
Loading Capacity	40'HQ	Stes	304	235	196	134	111