PAX RC



4 Key Remote Control



- Two-way communication
- 2 operational buttons arm/disarm and 2 programmable buttons
- Key lock function

PAX RC is a 4 button remote control. PAX RC is a fully configurable high-performance wireless remote control. The two-way communication allows a visual (LED) confirmation to be displayed for the commands sent to the control panel.

PAX RC is compatible for operation with:

- BRAVO Next wireless control panel, for building of fully wireless security systems.
- · PAX WL Expander module, for building of hybrid security systems with Eclipse series control panels.

The exceptional performance of the remote control is possible, thanks to our improved wireless communication protocol Beacon+.

Features

- Bi-directional type for wireless communication
- Jamming detection and communication channels encryption
- Wireless communication range(open space) up to 1500m
- Standard type of batteries CR2450
- Functions: Arm, Disarm
- Two buttons with programmable functionality
- Key lock function

Technical Specifications

Communication type: Bi-directional Wireless communication range (open space): Low voltage threshold 2.6 V Absorbed current (TX / Standby) EMC Immunity EN 50130-4 Battery 1x3V/600mAh, CR2450 type Battery life ~ 4 years Operating temperature range: from -10°C to +50°C Enclosure box: ABS plastic, white Dimensions 66 x 35 x 12 mm	Operation frequency:	~ 868MHz
range (open space): Low voltage threshold 2.6 V Absorbed current (TX / Standby) 16 mA / 2 µA EMC Immunity EN 50130-4 Battery 1x3V/600mAh, CR2450 type Battery life ~ 4 years Operating temperature range: from -10°C to +50°C Enclosure box: ABS plastic, white	Communication type:	Bi-directional
Absorbed current (TX / Standby) EMC Immunity EN 50130-4 Battery Battery CR2450 type Battery life A years Operating temperature range: Enclosure box: ABS plastic, white	range (open	up to 1500m
Standby) EMC Immunity EN 50130-4 Battery CR2450 type Battery life A years Operating temperature range: Enclosure box: ABS plastic, white	Low voltage threshold	2.6 V
Battery Description Battery life A years Operating temperature range: Enclosure box: ABS plastic, white	*	16 mA/2 µA
Battery CR2450 type Battery life ~ 4 years Operating temperature range: from -10°C to +50°C Enclosure box: ABS plastic, white	EMC Immunity	EN 50130-4
Operating temperature range: from -10°C to +50°C Enclosure box: ABS plastic, white	Battery	
range: Enclosure box: ABS plastic, white	Battery life	~ 4 years
		from -10°C to +50°C
Dimensions 66 x 35 x 12 mm	Enclosure box:	ABS plastic, white
	Dimensions	66 x 35 x 12 mm

Last update: 03. 2023



