

Wireless Indoor Siren



- Powerful piezoelectric siren
- Indoor application
- Compact size and modern design

PAX SR INTR is a wireless siren for indoor mounting. The siren is compatible for operation with:

- BRAVO Next wireless control panel, for building of fully wireless security systems.
- PAX WL Expander module, for building of hybrid security systems with Eclipse series control panels.

Features

- Bi-directional type for wireless communication
- Jamming detection and communication channels encryption
- Wireless communication range (open space) - up to 1500m
- Signal strength indication (RSSI)
- Comfort LEDs for various status indications (red and green)
- Adjustable alarm tone volume - 4 levels
- Acoustic pressure: 102dB/1m
- Long battery life - ~ 7 years
- Indoor Use
- Compact size

Technical Specifications

Operation frequency:	~ 868MHz
Communication type:	Bi-directional
Radio distance (open space):	up to 1500m
Sound level	102dB/1m
Alarm tone duration (programmable)	1-3min
Tone frequency range	2700-3300Hz
EMC Immunity	EN50130-4:2011+A1:2014
Battery (battery package)	4 x 3V CRI7450 package
Battery life	~7 years
Operating temperature range:	from -10°C to +50°C
Enclosure box:	ABS plastic, white
Dimensions	110 x 58 mm

Last update: 03. 2023