PAX SR EXT



Wireless Outdoor Siren



- Adjustable alarm tone level
- Squawk functionality Activation / deactivation tones
- LED Indicator light
- Internal metal cover

PAX SR EXT is a wireless piezo siren for outdoor usage. The siren is compatible for operation with:

- · BRAVO Next wireless control panel, for building of fully wireless security systems.
- · PAX WL Expander module, for building of hybrid security systems with Eclipse series control panels.

PAX SR EXT is equipped with sound and LED indication for announcing of alarm events, inner metal cover and bidirectional tamper for higher protection.

The siren has a flat plastic cover, which is especially suitable for company sticker or logo.

Features

- Bi-directional type of wireless communication
- Jamming detection and communication channels encryption
- Signal strength indication (RSSI)
- Two-way tamper switch for selfprotection of the box
- Squawk functionality Activation / deactivation tones
- Internal metal cover for better protection
- Plastic cover for protection of the electronic components
- Adjustable alarm tone volume 4 levels

Technical Specifications

| Operation frequency: | ~ 868MHz |
|---|------------------------|
| Communication type: | Bi-directional |
| Radio distance (open space): | up to 1500m |
| Sound pressure level | 102db@1m |
| Max. Alarm tone duration (programmable) | 1 - 3 min |
| Tone frequency range | 2700-3300Hz |
| EMC Immunity | EN 50130-4 |
| Battery pack | 4x3V Li - size A |
| Battery life | ~ 7 years |
| Operating temperature range: | from -25°C to +65°C |
| IK protection rating | IK08 |
| IP protection rating | IP45 |
| Enclosure box: | ABS plastic, white |
| Dimensions | 309 x 197 x 40 mm |
| | |

Last update: 03. 2023



