

# S200-6TP-AC-C

## MAIN FEATURES



**6x10/100Base-T RJ45**

**Unmanaged PoE Switch**

**Input Voltage:** AC 100-240V 50/60 Hz

**Operating Temperature:** -10°C ~ +50°C

**Thermal Methods:** Fanless design

**Surge Protection:** 2-6KV

**Test Report:** CCC, RoHS, FCC, CE

## PRODUCT DESCRIPTION

S200-6TP-AC-C series is non management PoE switch with 6x10/100Mbps adaptive RJ45 ports, port 1-4 support PoE/PoE+, total 50W PoE consumption, port 5&port 6 are 10/100Mbps uplink ports. Each RJ45 port supports MDI/MDIX and wire speed forwarding functions. Store and forward to provide stable and reliable data transmission.

## PRODUCT PARAMETERS

Fix Ports	
Fixed port	6x10/100Base-T
Power interface	AC100-240V triangle interface
LED Indicators	P , Active
Cable Type & Transmission Distance	
Twisted-pair	0-100m/ 250m
Network Topology	
Ring topology	Not Support
Star topology	Support
Bus topology	Support
Tree Topology	Support

**Scodena**

<b>Electrical Specifications</b>	
Input voltage	AC 100-240V 50/60Hz
Total Power consumption	<52W(PoE)
Main board power	<2W
<b>PoE</b>	
PoE protocol	802.3AF, 802.3AT
Pin Assignment	12+ 36-
Pin port	1-4
<b>Dialing switch Instruction</b>	
1 extend	250m long distance transmission
2 standard	Standard mode
3 port isolation	1-4 port port isolation
<b>Layer 2 Switching</b>	
Switching capacity	1.2G
Packet forwarding rate	0.89Mpps
MAC address table	2K
Buffer	768k bit
Jumbo frame	2K bytes
Forwarding delay	<5us
MDX/MIDX	Support
Storm control	Support
<b>Environment</b>	
Operating temperature	-10°C~+50°C
Storage temperature	-40°C~+70°C
Relative humidity	5%~90% (non-condensing)
Thermal methods	Fanless design, natural heat dissipation
MTBF	100,000 hours
<b>EMC &amp; Ingress Protection</b>	
Surge protection of Power	Common mode 4KV, differential-mode 2KV
Surge protection of Ethernet port	Common mode 6KV, differential-mode 2KV
ESD	Contact 8KV, Air 15KV
Free fall	0.5m
<b>Mechanical Dimensions</b>	
Product size	190*140*44mm (LxWxH)
Installation Method	Desktop
Weight	0.6KG
<b>Packing List</b>	
Packing list	Device, Inspection Certificate, User manual, Power cord
<b>Order Information</b>	
S200-6TP-AC 52W	4*10/100M RJ45 POE, 2*10/100M RJ45 uplink, built-in 52W power supply

S200-6TP-AC 72W

4\*10/100M RJ45 POE, 2\*10/100M RJ45 uplink,  
built-in 72W power supply

## SIZE AND APPEARANCE

